

# NATURAL 12 Bar 500mm CRV-PTS 230V

GRADE 304 Stainless Steel

Model/SKU: NAT12222-PTS-####\*

(\*where #### is the relevant finish code)

## HTR Technical Specifications:

Size: 518mm (width) x 1235mm (height)

Power: 150 Watts

Current: 0.65 Amps

Volts: 230 VAC

IP Rating: IPX5

**Controller Fitted:** PTSelect Switch (PTS)

## Controller Features:

- Temperature Adjustment • ON / OFF Switch • RED LED Indicator

## Controller Technical Specifications:

INPUT Voltage Range: 190VAC~250VAC

Operating Frequency: 50 Hz  $\pm$ 2%

Load Capability: 0.18A~4A

Load Control Range: 40~100%

Standby Current: 3.0mA


Suggested Height of Electrical Outlet = 750mm

(this is only an indication as every installation is different)

## NOTES:

\*EO Denotes DUAL ENTRY Electrical Outlet connection

\*PTS Denotes location of PTSelect Switch




Dimensions given are in mm. Bathroom Butler® reserves the right to alter and/or remove designs from time to time without prior notice. This drawing is to be used for reference purposes only. E & O.E.

Copyright Bathroom Butler® 2021

**BB™** BATHROOM  
BUTLER

USA: 631.464.2851 • [customercare@bathroombutler.com](mailto:customercare@bathroombutler.com) • [www.bathroombutler.com/us](http://www.bathroombutler.com/us)  
South Africa: 0860 104 653 • [info@bathroombutler.co.za](mailto:info@bathroombutler.co.za) • [www.bathroombutler.com/za](http://www.bathroombutler.com/za)  
Australia: +61 436 487 420 • [info\\_au@bathroombutler.com](mailto:info_au@bathroombutler.com) • [www.bathroombutler.com/au](http://www.bathroombutler.com/au)  
Mauritius: 230 242 1248 • [sales@lisinggroup.com](mailto:sales@lisinggroup.com) • [www.bathroombutler.com](http://www.bathroombutler.com)



Document version **033**

Product version **030**